


Wall & ceiling lighting fitting

5905339291219



MO
DE
RN
design



Kanlux LAURIN spotlights provide a very large selection of directional ceiling and wall lamps. The simple and minimalist design can be successfully used in many rooms in the house. Free adjustment of the luminous flux direction is an additional advantage of these fixtures.

GENERAL DATA:

Colour: black
Place of assembly: wall mounted, ceiling mounted
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Light source included: no
Length [mm]: 110
Width [mm]: 70
Height [mm]: 110

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: max 35
Class of protection against electric shock: I
Light source: PAR16
Cap: GU10
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: aluminum alloy
Connection type: Bolt terminal block
Range of sections of wires used [mm²]: 1÷2,5
The fixture is movable horizontally [°]: 310
The fixture is movable vertically [°]: 90
IP class: 20

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 20
Number of units in the secondary packaging: 1
Number of units in the packaging: 20
Net unit weight [g]: 250
Grammage [g]: 311.5
Length of a unit pack [cm]: 12
Width of a unit pack [cm]: 8
Height of a unit pack [cm]: 12
Weight of a cardboard box [kg]: 6.23
Width of a cardboard box [cm]: 25
Height of a cardboard box [cm]: 25

Wall & ceiling lighting fitting



Length of a cardboard box [cm] : 42

Volume of a cardboard box [m³]: 0.02625