


DOWNLIGHT LED 18W ANTI-GLARE RGB+CCT FUT072



LED Downlight FUT072 RGB+CCT 18W AC100-240V MiLight/MiBoxer is a multi-color recessed luminaire for suspended ceilings. A special housing designed to eliminate the glare effect, has a light beam angle of 60 °. The ability to smoothly adjust the brightness, color of light, and the color temperature of white light in the range of 2700-6500K. Control via a remote control or smartphone application (Wi-Fi bridge WL-BOX1 required). The LED luminaire acts as a repeater, while maintaining a 30m spacing between successive elements, allows for unlimited range.

Compatible products



Specification

Parameter	Value
Symbol	FUT072
ETIM CLASS	Downlight/spot/floodlight
Nominal voltage [V]	100 - 240
Voltage type	AC
Dimmable	yes
Luminous flux [lm]	1200
Colour temperature [K]	2700 - 6500
Power [W]	18
Power for white light [W]	18
Beam angle	Wide beam 41 - 80°
Colour rendering index CRI	CRI80

Power factor	>0.5
Colour of light	RGB+CCT
With movement sensor	yes
With light sensor	yes
Lamp type	LED not exchangeable
Lamp efficacy [lm/W]	75
Diameter [mm]	140
Height/depth [mm]	97
Weight [kg]	0.55