

# OPTIBAR CCT

SLI047400CCT\_PW

LED luminaire OPTIBAR CCT with the possibility of changing the light color (CCT), with a power of 12-42 W, high light efficacy 125 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000/4000/6000K, we can adjust the light color depending on our needs and preferences. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Narrow beam angle 90° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



Power	<b>12-42 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5250 lm (360°)</b>	Colour temperature	<b>3000/4000/6000 K</b>
Colour of light	<b>CCT</b>	Beam angle	<b>90 °</b>
Degree of protection (IP)	<b>IP20</b>		

## Technical data


Code	SLI047400CCT_PW
Power	12-42 W
Nominal current	170 mA
Voltage	230 V
Energy consumption	42 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.95
Useful luminous flux*	5250 lm (360°)
Luminous flux**	1450-5000 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	90 °
RA	90
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	1200x60x90 mm
For use	Inside
Assembly method	on track 3-fazowy
Application	Inside
Made in	PRC
Other	Light color change function 3000K/4000K/6000K ,

## Logistics data


Bulk packaging	12 pcs.
Quantity per pallet	96 pcs.
Gross weight (1 pcs.)	1.43 kg

## Related documents



 User manual



 Declaration of Conformity



 Photometric file

