

LED STRIP 128LED/M • 24V • 8W • 6000K • IP20 • 1200LM • RA80 • 10MM



12W /m
24V DC
150 lm/W LM80 SDCM ≤ 3
6.25cm cutting length
3oz 10mm FPC
Ra>80, available over 95
75000h L70 lifespan
30m reel for IP20, 10m for IP66 / IP68
Warranty 3 years

High quality LED strip for professional use with seven LEDs in one module to achieve luminous efficacy up to 150 lm/W. Two layers of PCB with 3oz copper paths characterized by a lower voltage drop and lower operating temperature. On a base using adhesive tape 3M 300 LSE. LEDs that meet requirements of LM-80 test, guaranteeing small lumen decrease and colour constancy in time.

Specification

Parameter	Value
Symbol	SPE-128-CW-24
EAN13	5901289755283
ETIM CLASS	Light ribbon-/hose/-strip
Socket	wires
Model	Tape
Mains or non-mains	NMLS
Dimmable	yes
Power [W]	8
Power for white light [W]	8
Colour of light	White
Number of nodes per meter	128
Degree of protection	IP20
Suitable for use	
cutting length [cm]	6.25
Voltage [V]	24
Voltage type	DC
Colour temperature [K]	6000
Colour rendering index CRI	80
Energy efficiency class	D
Luminous flux [lm]	1200
Standby power consumption [W]	0
Beam angle [°]	120

Correspondence beam angle	Sphere 360°
Non-directional or directional	Non-directional light source NDLS
Survival factor	0.9
Lumen maintenance factor	0.96
With Self-adhesive	yes
The energy consumption - white light [kW/1000h]	8
Min. number of switching cycles	50000
Rated life time L70/B50 at 25 °C [h]	75000
Colour-tuneable light source (CTLS)	yes
Connected light source (CLS)	yes
High-luminance light source (HLLS)	yes
Anti-glare shield	yes
Width [mm]	10
Height/depth [mm]	1.4