

Facade luminaire

5905339292605



Kanlux BISO are facade fittings characterized by simple and attractive design. They can be used as a fitting for interiors (they have an appropriate CRI coefficient), at the same time they can be used on building facades (IP54). In Kanlux BISO holder light falling from the LED module is softly diffused on facade and a rear part of the holder.


### GENERAL DATA:

**Colour:** graphite  
**Place of assembly:** wall mounted  
**Place of application:** Indoors and outdoors  
**Minimum distance from the illuminated object:** 0,5m  
**Compatible with a dimmer:** no  
**Wykrywanie ruchu:** no  
**Length [mm]:** 220  
**Width [mm]:** 90  
**Height [mm]:** 80  
**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50  
**Power factor:** 0.5  
**Maximum power [W]:** 8  
**Class of protection against electric shock:** I  
**Diode type:** LED COB  
**Luminous flux [lm]:** 140  
**Colour temperature:** white  
**Correlated colour temperature [K]:** 4000  
**Colour consistency in McAdam ellipses:** ≤6  
**Colour rendering index:** 80  
**Service life [h]:** 25000  
**Number of on/off cycles:** ≥25000  
**Luminous efficiency of the lamp [lm/W]:** 18  
**Ambient temperature range to which the product can be exposed:** -15÷40  
**Enclosure material:** aluminum alloy  
**Protective glass material:** plastic  
**Connection type:** Bolt terminal block  
**Range of sections of wires used [mm<sup>2</sup>]:** 1,5÷2,5  
**Lamp-heating time [s]:** ≤1  
**Lamp-ignition time [s]:** ≤0,5  
**IP class:** 54

### Facade luminaire



#### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 20

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 20

**Net unit weight [g]:** 580

**Grammage [g]:** 686

**Length of a unit pack [cm]:** 23

**Width of a unit pack [cm]:** 9

**Height of a unit pack [cm]:** 10


**Weight of a cardboard box [kg]:** 13.72

**Width of a cardboard box [cm]:** 22

**Height of a cardboard box [cm]:** 48

**Length of a cardboard box [cm]:** 48

**Volume of a cardboard box [m<sup>3</sup>]:** 0.050688



KANLUX S.A. (kat 29260) BISO LED EL 8W-GR / LDC (Polar)

Luminaire: KANLUX S.A. (kat 29260) BISO LED EL 8W-GR  
Lamps: 1 x BISO LED EL 8W-GR

